



1. PART NO. EXPRESSION :

P I C 1 2 0 5 H P 4 R 7 M F - □ □
(a) (b) (c) (d) (e)(f) (g)

- (a) Series code
(b) Dimension code
(c) Type code

- (d) Inductance code : 4R7 = 4.70uH
(e) Tolerance code : M = $\pm 20\%$, Y = $\pm 30\%$
(f) F : RoHS Compliant
(g) 11~99 : Internal controlled number

2. CONFIGURATION & DIMENSIONS :




Recommended PC Board Pattern


Unit:m/m

A	B	C	D	E	G	H	L
13.5 \pm 0.5	12.5 \pm 0.3	4.8 \pm 0.2	2.3 \pm 0.3	4.7 \pm 0.3	8.0	5.0	14.2

3. SCHEMATIC :



4. MATERIALS :



- (a) Core
(b) Wire
(c) Terminal
(d) Ink
(e) Paint

5. GENERAL SPECIFICATION :

- Test Freq. : L : 100KHz/1.0V
- Operating Temp. : -40°C to +125°C
- Storage Temp. : -40°C to +125°C
- Humidity Range : 85 \pm 3% RH
- Heat Rated Current (I_{rms}) will cause the coil temperature rise approximately Δt of 40°C (keep 1min)
- Saturation Current (I_{sat}) will cause L₀ to drop 20%.
- Part Temperature (Ambient+Temp. Rise) : Should not exceed 125°C under worst case operating conditions.
- Storage condition (component in its packaging)
 - Temperature: -10 to 40°C
 - Humidity : 50~60% RH



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.



SUPERWORLD ELECTRONICS (S) PTE LTD

06.11.2015

6. ELECTRICAL CHARACTERISTICS :

Part No.	Inductance L0 (μ H) @ 0 A	I _{rms} (A) Typ.	I _{sat} (A) Typ.	DCR (m Ω) Typ. @ 25°C	DCR (m Ω) Max. @ 25°C
PIC1205HPR20MF	0.20	52	110	0.45	0.55
PIC1205HPR22MF	0.22	52	110	0.5	0.7
PIC1205HPR33MF	0.33	42	80	0.7	0.9
PIC1205HPR36MF	0.36	42	75	0.75	0.95
PIC1205HPR39MF	0.39	42	70	0.78	0.95
PIC1205HPR47MF	0.47	38	65	0.86	1.1
PIC1205HPR50MF	0.50	37	60	0.9	1.3
PIC1205HPR56MF	0.56	36	55	1.0	1.5
PIC1205HPR68MF	0.68	34	54	1.4	1.7
PIC1205HPR82MF	0.82	31	52	1.7	2.1
PIC1205HP1R0MF	1.00	29	50	1.85	2.5
PIC1205HP1R2MF	1.20	28	49	2.5	3
PIC1205HP1R5MF	1.50	27	48	2.8	3.3
PIC1205HP1R8MF	1.80	21	40	4.0	4.9
PIC1205HP2R2MF	2.20	20	32	4.2	5.5
PIC1205HP3R3MF	3.30	15	32	6.8	9.2
PIC1205HP4R7MF	4.70	12	27	11.4	15.0
PIC1205HP5R6MF	5.60	11.5	22	12.3	16.5
PIC1205HP6R0MF	6.00	11.5	21.5	13	16.5
PIC1205HP6R8MF	6.80	11	21	14.5	18.5
PIC1205HP8R2MF	8.20	9.5	18	16.8	22.5
PIC1205HP100MF	10.0	9.0	16	21.4	25.5
PIC1205HP150MF	15.0	8.2	13	32	38
PIC1205HP180MF	18.0	7.5	11	40	45
PIC1205HP220MF	22.0	6.5	10	50	58

Tolerance code : M = $\pm 20\%$, Y = $\pm 30\%$



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.







06.11.2015



SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 2

7. CHARACTERISTICS CURVES :



RoHS Compliant


NOTE : Specifications subject to change without notice. Please check our website for latest information.




SUPERWORLD ELECTRONICS (S) PTE LTD

06.11.2015


PIC1205HPR50MF




PIC1205HPR56MF




PIC1205HPR68MF




PIC1205HPR82MF



PIC1205HP1R0MF



PIC1205HP1R2MF



RoHS Compliant


NOTE : Specifications subject to change without notice. Please check our website for latest information.

06.11.2015




SUPERWORLD ELECTRONICS (S) PTE LTD


PIC1205HP1R5MF




PIC1205HP1R8MF




PIC1205HP2R2MF




PIC1205HP3R3MF



PIC1205HP4R7MF



PIC1205HP5R6MF



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.


06.11.2015




SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 5


PIC1205HP6R0MF




PIC1205HP6R8MF




PIC1205HP8R2MF




PIC1205HP100MF



PIC1205HP150MF



PIC1205HP180MF



RoHS Compliant


NOTE : Specifications subject to change without notice. Please check our website for latest information.

06.11.2015



SUPERWORLD ELECTRONICS (S) PTE LTD

PG.6



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

06.11.2015



SUPERWORLD ELECTRONICS (S) PTE LTD

8. SOLDERING

Mildly activated rosin fluxes are preferred. The minimum amount of solder can lead to damage from the stresses caused by the difference in coefficients of expansion between solder, chip and substrate. Our terminations are suitable for all re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

8-1.1 Solder Re-flow :

Recommended temperature profiles for re-flow soldering in Figure 1.

8-1.2 Soldering Iron (Figure 2) :

Products attachment with soldering iron is discouraged due to the inherent process control limitations.

In the event that a soldering iron must be employed the following precautions are recommended.

Note :

- Preheat circuit and products to 150°C.
- 355°C tip temperature (max)
- Never contact the ceramic with the iron tip
- 1.0mm tip diameter (max)
- Use a 20 watt soldering iron with tip diameter of 1.0mm
- Limit soldering time to 4~5 secs.




Figure 1. Re-flow Soldering: 3 times max.




Figure 2. Hand Soldering: 1 times max.



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.




SUPERWORLD ELECTRONICS (S) PTE LTD

06.11.2015

PG. 8


9. PACKAGING INFORMATION :

9-1. Reel Dimension



Type	A(mm)	B(mm)	C(mm)	D(mm)
13" x 24mm	24.4+2.0/-0	100±2	13.5±0.5	330

9-2. Tape Dimension



Series	Bo(mm)	Bz(mm)	Ao(mm)	Az(mm)	Ko(mm)	P(mm)	W(mm)	F(mm)	t(mm)
PIC1205	14.1±0.1	13.0±0.1	12.9±0.1	7.0±0.1	5.5±0.1	16.0±0.1	24±0.3	11.5±0.1	0.35±0.05

9-3. Packaging Quantity

Size	PIC1205
Chip / Reel	500
Inner Box	1000
Carton	4000



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.


06.11.2015



SUPERWORLD ELECTRONICS (S) PTE LTD

PG.9

9-4. Tearing Off Force



The force for tearing off cover tape is 10 to 130 grams in the arrow direction under the following conditions. (referenced ANSI/EIA-481-C-2003 of 4.11 standard)

Room Temp. (°C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed (mm/min)
5~35	45~85	860~1060	300

Application Notice

- 1. Storage Conditions :
To maintain the solderability of terminal electrodes :
 - a) Recommended products should be used within 12 months from the time of delivery.
 - b) The packaging material should be kept where no chlorine or sulfur exists in the air.
- 2. Transportation :
 - a) Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
 - b) Vacuum pick up is strongly recommended for individual components.
 - c) Bulk handling should ensure that abrasion and mechanical shock are minimized.



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

06.11.2015



SUPERWORLD ELECTRONICS (S) PTE LTD