

1. PART NO. EXPRESSION :

Z 0 K 2 2 0 - R E - □ □
(a)(b)(c) (d) (e)(f) (g)

(a) Series code

(b) Dimension code

(c) Material code

(d) Impedance code : 220 = 22.0Ω




(e) R : Reel

(f) Current : E = 500mA

(g) 10: Standard

11 ~ 99 : Internal control number

2. CONFIGURATION & DIMENSIONS :




Recommended PC Board Pattern




Unit: mm

A	B	C	D	G	H	L
0.60± 0.03	0.30± 0.03	0.30± 0.03	0.15± 0.05	0.30 Ref.	0.30 Ref.	0.80 Ref.

3. SCHEMATIC :



4. MATERIALS :



(a) Body : Ferrite

(b) Termination : Ag/Ni/Sn

5. GENERAL SPECIFICATION :

a) Operating temp. : -40° C to +125° C (including self-temperature. rise)

b) Storage condition (component in its packaging)

i) Temperature : -10 to 40° C

ii) Humidity : 60%



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.



SUPERWORLD ELECTRONICS (S) PTE LTD

19.01.2015

PG. 1

6. ELECTRICAL CHARACTERISTICS :

Part Number	Impedance (Ω)	Test Frequency (MHz)	DC Resistance (Ω) Max.	Rated Current (mA) Max.
Z0K220-RE-10	22 $\pm$ 25%	100	0.065	500
Z0K330-RE-10	33 $\pm$ 25%	100	0.07	500
Z0K800-RB-10	80 $\pm$ 25%	100	0.40	200
Z0K121-RB-10	120 $\pm$ 25%	100	0.45	200
Z0K241-RB-10	240 $\pm$ 25%	100	0.65	200
Z0K601-RB-10	600 $\pm$ 25%	100	1.20	150
Z0H600-RB-10	60 $\pm$ 25%	100	0.25	200
Z0H121-RB-10	120 $\pm$ 25%	100	0.40	200
Z0H241-RB-10	240 $\pm$ 25%	100	0.80	200
Z0H471-RA-10	470 $\pm$ 25%	100	1.05	100
Z0H601-RA-10	600 $\pm$ 25%	100	1.20	100
Z0B100-RB-10	10 $\pm$ 25%	100	0.25	200
Z0B220-RB-10	22 $\pm$ 25%	100	0.45	200
Z0B330-RB-10	33 $\pm$ 25%	100	0.55	150
Z0B470-RB-10	47 $\pm$ 25%	100	0.70	150
Z0B560-RA-10	56 $\pm$ 25%	100	1.00	100
Z0B800-RA-10	80 $\pm$ 25%	100	1.30	100
Z0B121-RA-10	120 $\pm$ 25%	100	1.50	100



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

19.01.2015




SUPERWORLD ELECTRONICS (S) PTE LTD


PG. 2

7. CHARACTERISTICS CURVES :


Z0K220-RE-10




Z0K330-RE-10




Z0K800-RB-10




Z0K121-RB-10



Z0K241-RB-10



Z0K601-RB-10



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.




SUPERWORLD ELECTRONICS (S) PTE LTD


19.01.2015

PG. 3


Z0H600-RB-10




Z0H121-RB-10




Z0H241-RB-10




Z0H471-RA-10



Z0H601-RA-10



Z0B100-RB-10



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.


19.01.2015




SUPERWORLD ELECTRONICS (S) PTE LTD

PG. 4


Z0B220-RB-10




Z0B330-RB-10




Z0B470-RB-10




Z0B560-RA-10



Z0B800-RA-10



Z0B121-RA-10



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.




SUPERWORLD ELECTRONICS (S) PTE LTD

19.01.2015

PG. 5

8. SOLDERING AND MOUNTING :

8-1. Recommended PC Board Pattern



PC board should be designed so that products can prevent damage from mechanical stress when warping the board.

8-2. Soldering

Mildly activated rosin fluxes are preferred. The terminations are suitable for re-flow soldering systems. If hand soldering cannot be avoided, the preferred technique is the utilization of hot air soldering tools.

Note.

If wave soldering is used, there will be some risk.

Re-flow soldering temperatures below 240 degrees, there will be non-wetting risk

8-2.1 Lead Free Solder Re-flow :

Recommended temperature profiles for lead free re-flow soldering in Figure 1. (Referred to J-STD-020C)

8-2.2 Soldering Iron :

Products attachment with a soldering iron is discouraged due to the inherent process control limitations. If a soldering iron must be employed the following precautions are recommended. for Iron Soldering in Figure 2.

Note :

- a) Preheat circuit and products to 150° C.
- b) 350° C tip temperature for Ferrite chip bead (max)
- c) Never contact the ceramic with the iron tip
- d) 1.0mm tip diameter (max)
- e) Use a 20 watt soldering iron with tip diameter of 1.0mm
- f) Limit soldering time to 4-5 secs.




Figure 1. Re-flow Soldering:3 times max




Figure 2. Wave Soldering:1 times max

NOTE : Specifications subject to change without notice. Please check our website for latest information.



RoHS Compliant



SUPERWORLD ELECTRONICS (S) PTE LTD

19.01.2015

PG. 6

8-3. Solder Volume

Accordingly increasing the solder volume, the mechanical stress to product is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance. Solder shall be used not to be exceed as shown in Fig. 4.

Minimum fillet height = soldering thickness + 25% product height




Figure 4



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.

19.01.2015




SUPERWORLD ELECTRONICS (S) PTE LTD


PG. 7

9. PACKAGING INFORMATION :

9-1. Reel Dimension




Type	A(mm)	B(mm)	C(mm)	D(mm)
7" x 8mm	9.0±0.5	60.0±2.0	13.5±0.5	178.0±2.0
7" x 12mm	13.5±0.5	60.0±2.0	13.5±0.5	178.0±2.0




9-2.1 Tape Dimension / 8mm

Material of taping is paper




Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	t(mm)
0	0.68±0.05	0.38±0.05	0.50max	2.0±0.05	0.50max



Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	t(mm)
1	1.12±0.03	0.62±0.03	0.60±0.03	2.0±0.10	0.60±0.03
2	1.85±0.05	1.05±0.05	0.95±0.05	4.0±0.10	0.95±0.05
3(09)	2.30±0.05	1.50±0.05	0.95±0.05	4.0±0.10	0.95±0.05

Material of taping is plastic



Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	t(mm)	D1(mm)
2(08)	1.95±0.10	1.05±0.10	1.05±0.10	4.0±0.10	0.23±0.05	none
3(09)	2.25±0.10	1.42±0.10	1.04±0.10	4.0±0.10	0.22±0.05	1.0±0.10
3(12)	2.35±0.10	1.50±0.10	1.45±0.10	4.0±0.10	0.22±0.05	1.0±0.10
4(11)	3.50±0.10	1.88±0.10	1.27±0.10	4.0±0.10	0.22±0.05	1.0±0.10
5	3.42±0.10	2.77±0.10	1.55±0.10	4.0±0.10	0.22±0.05	1.0±0.10
4(09)	3.40±0.10	1.77±0.10	1.04±0.10	4.0±0.10	0.22±0.05	1.0±0.10



RoHS Compliant


NOTE : Specifications subject to change without notice. Please check our website for latest information.



SUPERWORLD ELECTRONICS (S) PTE LTD

19.01.2015

9-2.2 Tape Dimension / 12mm




Series	Size	Bo(mm)	Ao(mm)	Ko(mm)	P(mm)	t(mm)	D1(mm)
Z / L	6	4.95±0.1	1.93±0.1	1.93±0.1	4.0±0.1	0.24±0.05	1.5±0.1
	7	4.95±0.1	3.66±0.1	1.85±0.1	8.0±0.1	0.24±0.05	1.5±0.1

9-3. Packaging Quantity

Chip Size	7	6	5	4(11)	4(09)	3(12)	3(09)	2	1	0
Chip / Reel	1000	2000	2500	3000	3000	2000	4000	4000	10000	15000
Inner Box	4000	8000	12500	15000	15000	10000	20000	20000	50000	75000
Middle Box	20000	40000	62500	75000	75000	50000	100000	100000	250000	375000
Carton	40000	80000	125000	150000	150000	100000	200000	200000	500000	750000

9-4. Tearing Off Force



The force for tearing off cover tape is 15 to 60 grams in the arrow direction under the following conditions.

Room Temp. (° C)	Room Humidity (%)	Room atm (hPa)	Tearing Speed (mm/min)
5~35	45~85	860~1060	300

Application Notice

1. Storage Conditions :

To maintain the solderability of terminal electrodes :

- Recommended products should be used within 12 months from the time of delivery.
- The packaging material should be kept where no chlorine or sulfur exists in the air.

2. Transportation :

- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- The use of tweezers or vacuum pick up is strongly recommended for individual components.
- Bulk handling should ensure that abrasion and mechanical shock are minimized.



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.



SUPERWORLD ELECTRONICS (S) PTE LTD

19.01.2015