



1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE	VA	L	W	H	ML	A	B	C	Optional mtg. screw & nut*	gram
2	1.1	35.50 (1.40)	30.00 (1.180)	24.00 (0.95)	----	6.35 (.250)	6.35 (.250)	30.48 (1.200)	None	73

2. SCHEMATIC :



3. ELECTRICAL CHARACTERISTICS (@ 25°C) :

a. Primary Voltage	AC 115/230 V 50/60 Hz .
b. No Load Primary Current	Less Than 10mA .
Input AC 115V 60Hz .	Less Than 10mA .
Input AC 230V 50Hz .	Series AC 189.40V .
c. Secondary Voltage (±5%)	Parallel AC 94.70V .
d. Secondary Load Current	Series 0.01A .
	Parallel 0.02A .
e. Full Load Primary Current	Less Than 20mA .
Input AC 115V 60Hz .	Less Than 15mA .
Input AC 230V 50Hz .	Series 120.00V .
f. Full Load Secondary Voltage (±5%)	Parallel 60.00V .
g. DC Resistance	
Pin 1-2	Primary = 2236 Ohm .
Pin 3-4	= 3016 Ohm .
Pin 5-6	Secondary = 1770 Ohm .
Pin 7-8	= 2340 Ohm .
h. Insulation Resistance	DC 500V 100Meg Ohm Of More .
i. Withstand Voltage (Hi-Pot)	AC 2500V 60Hz 1 Minutes .
j. Temperature Rise	Less Than 60 Deg C .
k. Core Size	EI-35 x 7.00 m/m .



RoHS Compliant

NOTE : Specifications subject to change without notice. Please check our website for latest information.



15.01.2008