



## 1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE	VA	L	W	H	ML	A	B	C	Optional mtg. screw & nut*	gram
7	36	66.68 (2.625)	55.58 (2.188)	40.50 (1.600)	----	10.16 (.400)	10.16 (.400)	46.99 (1.850)	None	510

## 2. SCHEMATIC :



## 3. ELECTRICAL CHARACTERISTICS (@ 25°C) :

- |                                      |  |
|--------------------------------------|--|
| a. Primary Voltage                   | AC 115 V 60 Hz .                           |
| b. No Load Primary Current           | Less Than 60mA .                           |
| c. Secondary Voltage (±5%)           | Series AC 67.80V .<br>Parallel AC 33.90V . |
| d. Secondary Load Current            | Series 0.65A .<br>Parallel 1.30A .         |
| e. Full Load Primary Current         | Less Than 390mA .                          |
| f. Full Load Secondary Voltage (±5%) | Series 56.00V .<br>Parallel 28.00V .       |
| g. DC Resistance                     |  |
| Pin 1-4                              | Primary = 22.50 Ohm .                      |
| Pin 5-6                              | Secondary = - Ohm .                        |
| Pin 7-8                              | = - Ohm .                                  |
| h. Insulation Resistance             | DC 500V 100Meg Ohm Of More .               |
| i. Withstand Voltage (Hi-Pot)        | AC 2500V 60Hz 1 Minutes .                  |
| j. Temperature Rise                  | Less Than 60 Deg C .                       |
| k. Core Size                         | EI-66 x 16.00 m/m .                        |



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

15.01.2008



**SUPERWORLD ELECTRONICS (S) PTE LTD**