



Pin Type (VC)OCXO

JOX254H(V) HCMOS output



customer		date: 03-08-2024
customer item number		
project		
Jauch item number	252218	



RoHS compliant



Pb free



REACH compliant

SPECIFICATION	Min	Typical	Max	Unit	Condition
frequency		12.80		MHz	
operating temperature range	-40		+85	°C	temperature code K
freq. tolerance at 25 °C	-200		+200	ppb	see condition (1a)
freq. stability vs. temperature	-10		+10	ppb	stability code H, see condition (2a)
freq. stability vs. supply voltage change	-5		+5	ppb	at Vdc +/- 5%, see condition (3)
freq. stability vs. load change	-5		+5	ppb	at nom. load +/-5%, see condition (4)
aging (1st year)	-0.2		+0.2	ppm	at room temperature, see condition (6)
frequency drift at constant temperature	-2.0		+2.0	ppb	per day, at +25°C, see condition (7)
short term frequency stability (ADEV)		0.02		ppb	tau = 1 second, test after 1h at +25°C
supply voltage	3.13	3.30	3.47	V	Vdc +/- 5%
steady current consumption			250	mA	at 25°C
warm up current consumption			650	mA	
operable temperature range	-40		+85	°C	
storage temperature range	-55		+105	°C	
output waveform		HCMOS			
output load		15		pF	nominal load
output low level			0.4	V	
output high level	2.4			V	
output rise & fall time			10	ns	at 10% <-> 90% of waveform
output symmetry	40	50	60	%	at 50% of waveform
phase noise		-120	-110	dBc / Hz	at 10 Hz from carrier
phase noise		-150	-140	dBc / Hz	at 100 Hz from carrier
phase noise		-165	-155	dBc / Hz	at 1 kHz from carrier
phase noise		-168	-158	dBc / Hz	at 10 kHz from carrier
phase noise		-168	-158	dBc / Hz	at 100 kHz from carrier
phase noise		-168	-158	dBc / Hz	at 1 MHz from carrier
moisture sensitivity level (MSL)		n.a.			not sensitive
packing unit		t.b.d.		pieces	per carton box

ORDER INFORMATION

O 12.80-JOX254H-3-H-K-RCAl-LF

NOTE

The definitions of test conditions can be found here:
https://www.jauch.com/downloadfile/659facd821fb884b5336556c0385aefc1/jauch_ocxo_test_definitions_1v0_20240111.pdf

MARKING INFORMATION


Jauch
frequency
model and spec code
date code (YY/WW)




Pin Type (VC)OCXO JOX254H(V) HCMOS output




DIMENSION in mm



top view



side view



bottom view


OCXO
JOX254
1: output
2: GND
3: NC
4: NC
5: V_{DC}

pin connection


VCOCXO
JOX254V
1: output
2: GND
3: $V_{Control}$
4: NC (option ref. voltage)
5: V_{DC}

in mm


TAPING SPECIFICATION in mm



buffer material



cardboard – max. 20 pcs



dimensions in mm