



Lithium-Iron-Phosphate Battery

LFP1216

- High Energy Density
- Long Cycle Life
- Replaceable with lead-acid systems
- light weight

SPECIFICATIONS	
Jauch part number	253075
Certification	UN 38.3, CE, RoHS, REACH
	Cell: UL1642, IEC62133

ELECTRIC

Nominal Voltage	12.8 V
Rated Capacity	16 Ah (C ₂₀)
Energy	204.8 Wh
Internal Resistance	≤ 50 mΩ
Cycles	2000 times ≥ 80% DOD
Self discharge	≤ 2%/Month

MECHANICAL

Casing Material	ABS
Flammability	UL94-V0
Configuration	4s4p 26650
Weight	~1.73kg
Terminal	T2

SPECIFICATIONS	
----------------	--

ENVIRONMENT

Charge temperature range	0°C ~ 45°C
Discharge temperature range	-20°C ~ 60°C
Storage temperature	0°C to + 60°C
IP protection level	IP54


STANDARD CHARGE

Charge voltage	14.4 V ± 0.15 V
Standard charge current	3.2 A
Maximum charge current	8 A
BMS charge cut-off voltage cell	3.9 V ± 0.05 V


STANDARD DISCHARGE

Discharge current	8 A
Maximum continual discharging currentcell	≤ 16 A
BMS discharge cut-off voltage cell	2.0 V ± 0.16 V

DIMENSIONS (mm)



CHARGE-DISCHARGE CURVE 0.2C, 25°C



DOD-CYCLES 0.2C, 25°C

